





Veriton 2000 Mid Tower





Product views	1. Power button 5. Three US	SB 3.2 Gen 1 ports and 8. Display port	12. COM (Serial) port (optional)
		3.2 Gen 1 Type C port 9. Two USB 2.0 ports	<ol><li>Ethernet (RJ-45) port</li></ol>
	<ol> <li>Status LEDs</li> <li>Audio ja</li> </ol>		<ol><li>Power connector</li></ol>
	4. Combo jack 7. HDMI® p	port 11. VGA port	
Operating system <sup>1, 2</sup>	DOS		
CPU and chipset <sup>1</sup>	S2720G:		
	Intel® Core™ i3 14th gen processors		
	Intel® H610 Chipset		
Memory <sup>1, 3, 4</sup>	8 GB DDR5 4800 MHz UDIMM		
0: 15	Up to 32 GB of Dual-channel DDR5 4800 MHz  Hard disk drive:	Solid state drive:	
Storage <sup>1, 5</sup>		• 256 GB M.2 2280 PCI-E Gen4 SSD	
	2 TB / 1 TB 3.5-inch 7200 RPM (Optional)  8X Super-Multi drive, 9.0 mm slim, tray-load	• 256 GB M.2 2280 PCI-E Gen4 SSD	
Optical media drive			
Graphics <sup>6</sup>	Intel Graphics		
Audio	Integrated high-definition sound, 5.1-channel surround	sound	
Communication	WLAN:		
	802.11ax/ac/a/b/g/n, Wi-Fi 6 and Bluetooth® 5		
	802.11ax/ac/a/b/g/n, Wi-Fi 6E and Bluetooth® 5		
Expansion slot(s)	PCle x16 slot(s): 1		
	PCle x1 slot(s): 1		
	M.2 slot (for SSD): 1 M.2 slot (for WLAN): 1		
Commercial features	TPM v2.0 (Trusted Platform Module)		
Commerciai reatures	Kensington lock slot		
	WOL (Wake On Lan)		
Commercial selected	Parallel (printer) port		
options	COM (Series) port		
	Internal speaker		
	Dust filter		
Dimensions	160 (W) x 306.32 (D) x 348.00 (H) mm (6.3 x 12.06 x 13.7	nches)	
Power supply and	Power supply:		
adapter	<ul> <li>300 W single-rail 12 V PFC (EuP), auto-sensing, 80PLL</li> </ul>		
	<ul> <li>300 W single-rail 12 V PFC (EuP), auto-sensing, 80PLL</li> </ul>	JS® Bronze, TFX	
	180 W PFC, auto-sensing, 80PLUS® Bronze, TFX		
System compliance	EPEAT® Silver (Spain), GS, ROHS, ENERGY STAR®		
Options and	Wireless (2.4 GHz RF) keyboard and mouse		
accessories	USB keyboard and mouse		
Certification	EPEAT Silver, BSMI, CE, FCC, CB		

- Specifications vary depending on model.
- 64-bit software is required to enjoy the advantages of 64-bit processing.

  A 64-bit operating system is required to enjoy the ultimate performance of 4 GB or higher memory. Memory speed may vary, depending on the CPU, chipset or memory fitted.
- $1\,GB$  is  $1\,D$  illion bytes. Actual formatted capacity is less and may vary depending on preloaded materials and operating environment. Recovery Management uses a portion of the stated hard disk capacity as dedicated
- Total available graphics memory comprises dedicated video memory, system memory, and shared system memory. This figure will vary depending on system memory, installed drivers, BIOS settings and other factors.

In a continuing effort to improve the quality of our products, information in this document is subject to change without notice. Images shown are only representations of some of the configurations available for this model. Availability may

In a continuing effort to improve the quality of our products, information in this document is subject to change without notice. Images shown are only representations of some of the configurations available for this model. Availability may vary depending on region.

As a phenomenon known to thin-film transistors (TFTs), liquid crystal displays (LCDs) commonly exhibit a small number of discoloration dots, as so-called "non-conforming pixels." This phenomenon is a limitation of TFT LCD technology, not a product defect, and as such is not covered by Acer's warranty.

© 2023. All rights reserved.

Microsoft and Windows are registered trademarks of Microsoft Corporation.

Ultrabook, Celeron, Inside, Intel, Intel Logo, Intel Arc graphics, Intel Atom, Intel Atom Inside, Intel Inside, Intel Inside Logo, Intel VPro, Intel Evo, Pentium, Pentium Inside, VPro Inside, Xeon, Xeon Inside, Intel Agilex, Arria, Cyclone, Movidius, eASIC, Ethernet, Iris, Killer, MAX, Select Solutions, Si Photonics, Stratix, Tofino, and Intel Optane are trademarks of Intel Corporation or its subsidiaries.