



Productivity Driven Solutions for Workflow Efficiency

Designed to meet small office and workgroup needs, the latest Canon imageCLASS LBP240 series printers are equipped with enhanced print speeds, scalable paper input capacity, versatile connectivity features and more.



QUICK 5.0 SEC FIRST PRINT OUT TIME





%10,200 PAGES HIGH-YIELD

MONO

*Applicable to LBP248x and LBP246dw



INTUITIVE TOUCHSCREEN DISPLAY*

Navigate and configure the printer settings easily with the 5" LCD touchscreen display. Information can be displayed at a glance, facilitating easy device management.

*Applicable to LBP248x



MULTIPLE PRINT ENVIRONMENT SUPPORT*

In addition to Canon's proprietary UFR II print language, industry standard PCL6 and Adobe® PostScript® 3™ print languages are supported to ensure seamless integration with a wide range of business applications.

*Applicable to LBP248x and LBP246dw.



EXPANDABLE PAPER CAPACITY

Designed to meet your growing business needs with an expandable paper capacity of up to 900 sheets. Suitable for handling multiple print jobs and minimising the frequency of replenishing paper.



DOCUMENT SECURITY*

Protect confidential documents with Secure Print. Jobs held at the printer are password-protected and are only released upon entry of password at printer.

*Applicable to LBP248x and LBP246dw.



SPECIFICATIONS

SPECIFICATIONS					
PRINT			imageCLASS LBP248x	imageCLASS LBP246dw	imageCLASS LBP243dw
Printing Method				Monochrome Laser Beam Printing	
	A4		40 ppm		36 ppm
Print Speed	Letter		42 ppm		37 ppm
	2-Sided		33 ipm (A4) / 35 ipm (Letter) 30 ipm (A4) / 31 ipm (Letter)		
Print Resolution			600 x 600 dpi		
Print Quality with Image Refinement Technology			1,200 x 1,200 (equivalent)		
Warm-Up Time (From Power On)			14 sec		
First Print Out Time (FPOT)	rst Print Out Time		5 sec		
Recovery Time (From Sleep Mode)			4 sec or less		
Print Language			UFR II, PCL 6, Adobe® PostScript® 3™ UFR II, PCL 6		
Auto Duplex Print			Yes		
Print Margins			Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)		
Comments of Etha Engage of Control of Contro		- A Dutus			
Supported File Format for USB Direct Print		ect Print	JPEG, TIFF, PDF N/A		
PAPER HANDLING					
Input Tray Capacity (Plain Paper, 80 g/m²)	Standard	Cassette	250 sheets		
		Multi Purpose Tray	100 sheets		
	C processing of the processing		550 sheets		
	Maximum		900 sheets (Standard + 1 Paper Feeder)		
Output Tray Capacity	(Plain Paper,	80 g/m²)	150 sheets		
Cassette / Paper Feeder		Paper Feeder	A4, A5, A6, B5, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Custom (min. 105 x 148 mm to max. 216 x 355.6 mm)		
Media Size	Multi Purpose Tray		A4, A5, A6, B5, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. 76.2 x 127 mm to max. 216 x 355.6 mm)		
	2-Sided Printing		A4, Legal, Letter, Foolscap, Indian Legal, Custom (min. 210 x 279.4 mm to max. 216 x 355.6mm)		
Media Type			Plain Paper, Recycled Paper, Label, Postcard, Envelope		
Cassette / Paper Feeder		Paper Feeder	60 – 120 g/m²		
Media Weight	dia Weight Multi Purpose Tray		60 – 199 g/m²		
CONNECTIVITY & SOFTWARE					
	Wired		USB 2.0, 10Base-T/100Base-TX/1000Base-T		
Standard Interfaces	Wireless		Wi-Fi 802:11b/g/n (Infrastructure Mode, WPS, Direct Connection)		
Network Protocol	ork Protocol Print		LPD, RAW, WSD-Print (IPv4, IPv6)		
Wired			IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE802.1X, IPsec, TLS 1.3		
etwork Security Wireless			Infrastructure Mode: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA2-EAP (AES) Access Point Mode: WPA2-PSK (AES)		
Mobile/Cloud Printing Solutions			Canon PRINT Business app, Canon Print Service (Android), AirPrint, Mopria, Microsoft Universal Print		
Operating System Compatibility*1			Windows 10/11, Windows Server 2012/2012 R2/2016/2019/2022, macOS 10:13 or later, Linux, Chrome OS		
Other Features			Department ID, Secure Print, Application Library Department ID, Secure Print Department ID		
Software Included			Department ID, Secure Print, Application Library Department ID, Secure Print Department ID Printer Driver, Toner Status		
GENERAL				Time Diver, foner status	
				1 GB	
Device Memory Display			5" LCD Touchscreen		LCD
Power Requirements					
			AC 220 – 240 V, 50/60 Hz		
Power Consumption	Operation		480 W (max. 1,250 W)		
	Standby		6 W		
	Sleep		0.9 W		
Operating Temperature		re	10 - 30°C		
Environment Humidity			20 – 80% RH (no condensation)		
Monthly Duty Cycle*2			80,000 pages		
Dimensions (W x D x H)			438 x 373 x 312 mm 399 x 373 x 249 mm		
Weight*3 (Approx.)			9.1 kg	8.71	· · · · · · · · · · · · · · · · · · ·
oner Cartridge*4			Cartridge 070 (Bundled: 3,		Cartridge 070: 3,000 pages (Bundled: 1,500 pages)
	High		Cartridge 070H : 10,200 pages		
OPTIONAL ACCESSO	RIES				
Paper Feeder			Cassette Feeding Unit-AH1 (550 sheets)		
Barcode Printing Kit			Barcode Printing Kit-E1E	-	



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS **CANON SINGAPORE PTE. LTD.**

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

¹¹ The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from the https://asia.canon/en/support website when available.

²² Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

Excluding toner cartridge.
 Toner cartridge yield is in accordance with ISO/IEC19752.